

## Acessório Electrosoldável PEAD


Fabricado em PE100-RC preto;

Voltagem de operação: 39,5 – 48V;

Adequado para redes de água (EN 12201 – ISO 4427).



**PN16  
SDR11**



dn	dn1	código	Z [mm]	Peso [Kg]
25	20	REP025020C	77	0,04
32	20	REP032020C	77	0,05
32	25	REP032025C	77	0,05
40	20	REP040020C	120	0,09
40	25	REP040025C	108	0,11
40	32	REP040032C	91	0,07
50	25	REP050025C	120	0,13
50	32	REP050032C	91	0,08
50	40	REP050040C	91	0,09
63	25	REP063025C	146	0,22
63	32	REP063032C	102	0,13
63	40	REP063040C	102	0,14
63	50	REP063050C	102	0,14
75	50	REP075050C	143	0,36
75	63	REP075063C	143	0,27
90	50	REP090050C	180	0,45
90	63	REP090063C	162	0,45
90	75	REP090075C	146	0,41
110	63	REP110063C	210	0,76
110	75	REP110075C	185	0,69
110	90	REP110090C	176	0,74
125	63	REP125063C	224	1,00
125	90	REP125090C	192	1,00
125	110	REP125110C	179	1,06
140	90	REP140090C	212	1,18
160	90	REP160090C	251	1,86
160	110	REP160110C	240	1,93
160	125	REP160125C	244	2,05
180	90	REP180090C	288	2,54
180	125	REP180125C	241	2,31
180	140	REP180140C	246	2,59
180	160	REP180160C	228	2,39
200	160	REP200160C	273	3,46
200	180	REP200180C	244	3,22
225	160	REP225160C	311	5,68
250	180	REP250180C	316	6,09
315	200	REP315200C	409	10,55