

Acessório Electrosoldável PEAD


Fabricado em PE100-RC preto;

Voltagem de operação: 39,5 – 48V;

Adequado para redes de água (EN 12201 – ISO 4427).




PN6 SDR26



* Soldadura dupla

dn	código	DE [mm]	Z [mm]	Peso [Kg]
110	MP110A	129	150	0,45
125	MP125A	143	158	0,55
140	MP140A	160	166	0,70
160	MP160A	184	184	1,00
180	MP180A	206	181	1,24
200	MP200A	229	210	1,73
225	MP225A	254	200	1,90
250	MP250A	278	210	2,05
280	MP280A	320	227	3,57
315	MP315A	360	247	4,35
355	MP355A	406	280	6,97
400	MP400A	458	325	9,47
450	MP450A	508	382	14,00
500	MP500A	570	385	20,25
560	MP560A	635	455	25,50
630	MP630A	690	436	24,50
710•	MP710A	776	450	32,65
800•	MP800A	872	455	39,20
900•	MP900A	982	500	59,00
1000•	MP1000A	1120	450	71,00
1100•	MP1100A	1200	450	77,00
1200•	MP1200A	1335	465	90,00
1400•	MP1400A	-	-	-

PN10 SDR17



dn	código	DE [mm]	Z [mm]	Peso [Kg]
90	MP090B	104	130	0,27
110	MP110B	129	150	0,45
125	MP125B	143	158	0,55
140	MP140B	160	166	0,70
160	MP160B	184	184	1,00
180	MP180B	206	181	1,24
200	MP200B	229	210	1,73
225	MP225B	254	200	1,92
250	MP250B	285	218	2,67
280	MP280B	320	227	3,57
315	MP315B	360	247	4,35
355	MP355B	406	280	6,97
400	MP400B	458	325	9,47
450	MP450B	508	382	14,00

Continua na próxima página...

Acessório Electrosoldável PEAD


Fabricado em PE100-RC preto;

Voltagem de operação: 39,5 – 48V;

Adequado para redes de água (EN 12201 – ISO 4427).




PN10 SDR17



dn	código	DE [mm]	Z [mm]	Peso [Kg]
500	MP500B	570	385	20,25
560•	MP560B	635	455	25,50
630•	MP630B	718	502	35,30
710•	MP710B	811	500	55,60
800•	MP800B	915	500	80,20
900•	MP900B	1013	520	82,20
1000•	MP1000B	1135	535	105,00
1100•	MP1100B	1240	540	131,40
1200•	MP1200B	1365	600	178,50

* Soldadura dupla

PN16 SDR11



dn	código	DE [mm]	Z [mm]	Peso [Kg]
20	MP020C	29	77	0,03
25	MP025C	34	77	0,04
32	MP032C	44	88	0,07
40	MP040C	55	94	0,10
50	MP050C	66	97	0,14
63	MP063C	78	113	0,18
75	MP075C	95	120	0,27
90	MP090C	111	129	0,39
110	MP110C	136	150	0,62
125	MP125C	155	154	0,90
140	MP140C	173	170	1,12
160	MP160C	197	185	1,52
180	MP180C	222	188	2,02
200	MP200C	246	210	2,79
225	MP225C	277	226	3,57
250	MP250C	310	242	4,85
280	MP280C	348	250	6,85
315	MP315C	387	266	8,79
355	MP355C	438	300	13,22
400	MP400C	488	352	18,90
450•	MP450C	542	425	26,47
500•	MP500C	600	457	34,00
560•	MP560C	700	500	54,38
630•	MP630C	780	505	65,10
710•	MP710C	855	525	89,40
800•	MP800C	950	520	112,80
900•	MP900C	1105	580	161,00
1000•	MP1000C	-	-	-
1200•	MP1200C	-	-	-

* Soldadura dupla

Acessório Electrosoldável PEAD


Fabricado em PE100-RC preto;

Voltagem de operação: 39,5 – 48V;

Adequado para redes de água (EN 12201 – ISO 4427).



**PN25
SDR7,4**



* Soldadura dupla

dn	código	DE [mm]	Z [mm]	Peso [Kg]
32	MP032H	44	88	0,07
40	MP040H	54	94	0,11
50	MP050H	66	97	0,14
63	MP063H	88	114	0,31
75	MP075H	105	118	0,46
90	MP090H	125	132	0,54
110	MP110H	150	150	0,94
125	MP125H	174	164	1,56
140	MP140H	193	168	2,10
160	MP160H	219	200	2,73
180	MP180H	240	201	3,07
200	MP200H	267	232	4,28
225	MP225H	311	239	8,27
250	MP250H	336	265	9,40
280	MP280H	386	270	11,16
315	MP315H	435	300	18,85
355	MP355H	496	356	28,90
400	MP400H	570	385	43,00
450	MP450H	-	-	-
500	MP500H	-	-	-