


Redução curta
 Reducción mango largo
 Réduction embout long
 Reduktion zentrisch, lange Schweißenden



Fabricado por molde
 Fabriqué par moulage

Fabricado mediante moldeo
 Produziert mit Spritzgußverfahren

SDR26 PN6



dn	dn1	código	H [mm]	H1 [mm]	Z [mm]	Peso [Kg]
250	160	RCP250160A	58	55	163	1,00
250	180	RCP250180A	62	50	155	1,00
250	200	RCP250200A	58	50	140	1,00
250	225	RCP250225A	50	68	150	1,00
280	200	RCP280200A	71	50	161	1,49
280	225	RCP280225A	71	55	154	1,48
280	250	RCP280250A	71	63	148	1,33
315	225	RCP315225A	80	55	184	2,12
315	250	RCP315250A	80	63	179	1,97
315	280	RCP315280A	80	75	174	1,86
355	225	RCP355225A	90	55	213	2,65
355	250	RCP355250A	86	63	196	2,53
355	280	RCP355280A	86	75	200	3,10
355	315	RCP355315A	86	84	187	3,00
400	280	RCP400280A	95	75	227	4,34
400	315	RCP400315A	95	84	222	4,30
400	355	RCP400355A	95	93	209	4,10
450	315	RCP450315A	62	84	224	4,60
450	355	RCP450355A	62	93	204	4,60
450	400	RCP450400A	62	98	190	4,60
500	355	RCP500355A	60	93	230	5,90
500	400	RCP500400A	60	98	210	6,30
500	450	RCP500450A	60	65	165	6,00
560	400	RCP560400A	53	98	240	8,40
560	450	RCP560450A	57	65	185	7,60
560	500	RCP560500A	57	67	163	6,90
630	450	RCP630450A	58	65	230	10,60
630	500	RCP630500A	63	62	206	11,42
630	560	RCP630560A	63	63	186	9,90
710	560	RCP710560A	65	40	160	13,80
710	630	RCP710630A	65	62	160	12,10
800	710	RCP800710A	62	60	160	14,30
900	800	RCP900800A	62	62	165	18,60
1000	900	RCP1000900A	65	56	170	22,00
1200	1000	RCP12001000A	58	45	165	32,70


Redução curta
 Reducción mango largo
 Réduction embout long
 Reduktion zentrisch, lange Schweißenden

Fabricado por molde
 Fabriqué par moulage

Fabricado mediante moldeo
 Produziert mit Spritzgußverfahren



SDR17 PN10



dn	dn1	código	H [mm]	H1 [mm]	Z [mm]	Peso [Kg]
250	160	RCP250160B	58	55	163	1,50
250	180	RCP250180B	62	50	155	1,95
250	200	RCP250200B	58	50	140	1,68
250	225	RCP250225B	50	68	150	1,66
280	200	RCP280200B	71	50	161	1,94
280	225	RCP280225B	71	55	154	1,94
280	250	RCP280250B	71	63	148	1,96
315	225	RCP315225B	80	55	184	2,87
315	250	RCP315250B	80	63	179	2,90
315	280	RCP315280B	80	75	174	2,87
355	225	RCP355225B	90	55	213	4,00
355	250	RCP355250B	86	63	196	3,80
355	280	RCP355280B	86	75	200	4,00
355	315	RCP355315B	86	84	187	4,00
400	280	RCP400280B	95	75	227	5,40
400	315	RCP400315B	95	84	222	5,60
400	355	RCP400355B	95	93	209	5,60
450	315	RCP450315B	62	84	224	6,40
450	355	RCP450355B	62	93	204	6,20
450	400	RCP450400B	62	98	190	6,60
500	355	RCP500355B	60	93	230	8,40
500	400	RCP500400B	60	98	210	8,40
500	450	RCP500450B	60	65	165	7,40
560	400	RCP560400B	53	98	240	10,80
560	450	RCP560450B	57	65	185	9,40
560	500	RCP560500B	57	67	163	8,80
630	450	RCP630450B	58	65	230	13,80
630	500	RCP630500B	63	62	206	13,40
630	560	RCP630560B	63	63	186	12,00
710	560	RCP710560B	65	40	160	15,05
710	630	RCP710630B	65	62	160	14,60
800	710	RCP800710B	62	60	160	18,80
900	800	RCP900800B	62	62	165	27,77
1000	900	RCP1000900B	65	56	170	29,60
1200	1000	RCP12001000B	58	45	165	45,00


Redução curta
 Reducción mango largo
 Réduction embout long
 Reduktion zentrisch, lange Schweißenden



Fabricado por molde
 Fabriqué par moulage

Fabricado mediante moldeo
 Produziert mit Spritzgußverfahren

SDR11 PN16



dn	dn1	código	H [mm]	H1 [mm]	Z [mm]	Peso [Kg]
250	160	RCP250160C	58	55	163	2,11
250	180	RCP250180C	62	50	155	2,36
250	200	RCP250200C	58	50	140	2,02
250	225	RCP250225C	50	68	142	2,17
280	200	RCP280200C	71	50	161	2,80
280	225	RCP280225C	71	55	154	2,81
280	250	RCP280250C	71	63	148	2,87
315	225	RCP315225C	80	55	184	4,01
315	250	RCP315250C	80	63	179	4,02
315	280	RCP315280C	80	75	174	4,11
355	225	RCP355225C	90	55	213	5,80
355	250	RCP355250C	86	63	196	5,40
355	280	RCP355280C	86	75	200	5,82
355	315	RCP355315C	86	84	187	5,60
400	280	RCP400280C	95	75	227	7,80
400	315	RCP400315C	95	84	222	8,20
400	355	RCP400355C	95	93	209	8,00
450	315	RCP450315C	62	84	224	8,10
450	355	RCP450355C	62	93	204	9,00
450	400	RCP450400C	62	98	190	9,20
500	355	RCP500355C	60	93	230	11,80
500	400	RCP500400C	60	98	210	11,60
500	450	RCP500450C	60	65	165	11,65
560	400	RCP560400C	53	98	240	15,20
560	450	RCP560450C	57	65	185	13,20
560	500	RCP560500C	57	67	163	12,34
630	450	RCP630450C	58	65	230	19,20
630	500	RCP630500C	63	62	206	18,40
630	560	RCP630560C	63	63	186	17,40
710	560	RCP710560C	65	40	160	21,20
710	630	RCP710630C	65	62	160	21,00
800	710	RCP800710C	62	60	160	26,60
900	800	RCP900800C	62	62	165	33,60
1000	900	RCP1000900C	65	56	170	42,80


Redução curta
 Reducción mango largo
 Réduction embout long
 Reduktion zentrisch, lange Schweißenden



Fabricado por molde
 Fabriqué par moulage


Fabricado mediante moldeo
 Produziert mit Spritzgußverfahren

SDR9 PN20



dn	dn1	código	H [mm]	H1 [mm]	Z [mm]	Peso [Kg]
250	160	RCP250160G	58	55	163	2,46
250	180	RCP250180G	62	50	155	2,23
250	200	RCP250200G	58	50	140	2,30
250	225	RCP250225G	50	68	150	2,14
280	200	RCP280200G	71	50	161	3,22
280	225	RCP280225G	71	55	154	3,29
280	250	RCP280250G	71	63	148	3,32
315	225	RCP315225G	80	55	184	4,80
315	250	RCP315250G	80	63	179	4,64
315	280	RCP315280G	80	75	174	5,01
355	250	RCP355250G	86	63	196	6,00
355	280	RCP355280G	86	75	200	6,40
355	315	RCP355315G	86	84	187	6,50
400	280	RCP400280G	95	75	227	9,20
400	315	RCP400315G	95	84	222	8,84
400	355	RCP400355G	95	93	209	9,20
450	315	RCP450315G	62	84	224	11,00
450	355	RCP450355G	62	93	204	9,98
450	400	RCP450400G	62	98	190	10,60
500	355	RCP500355G	60	93	230	12,09
500	450	RCP500450G	60	65	165	11,42
560	400	RCP560400G	53	98	240	17,32
560	450	RCP560450G	57	65	185	15,80
630	500	RCP630500G	63	62	206	18,65

SDR7,4 PN25



dn	dn1	código	H [mm]	H1 [mm]	Z [mm]	Peso [Kg]
250	160	RCP250160H	58	55	163	2,84
250	180	RCP250180H	62	50	155	2,62
250	200	RCP250200H	58	50	140	2,90
250	225	RCP250225H	50	68	150	2,54
280	200	RCP280200H	71	50	161	3,07
280	225	RCP280225H	71	55	154	3,60
280	250	RCP280250H	71	63	148	3,93
315	225	RCP315225H	80	55	184	4,64
315	250	RCP315250H	80	63	179	5,85
315	280	RCP315280H	80	75	174	5,84
355	250	RCP355250H	86	63	196	7,60
355	280	RCP355280H	86	75	200	8,00
355	315	RCP355315H	86	84	187	7,80

Ver próxima página
 Lisez la page suivante

Leer la página siguiente
 Siehe nächste Seite

Redução curta
 Reducción mango largo
 Réduction embout long
 Reduktion zentrisch, lange Schweißenden



Fabricado por molde
 Fabriqué par moulage

Fabricado mediante moldeo
 Produziert mit Spritzgußverfahren

SDR7,4 PN25



dn	dn1	código	H [mm]	H1 [mm]	Z [mm]	Peso [Kg]
400	280	RCP400280H	95	75	227	10,40
400	315	RCP400315H	95	84	222	11,00
400	355	RCP400355H	95	93	209	11,20
450	315	RCP450315H	62	84	224	-
450	355	RCP450355H	62	93	204	12,15
450	400	RCP450400H	62	98	190	12,30
500	450	RCP500450H	60	65	165	13,50
560	400	RCP560400H	53	98	240	19,90
560	450	RCP560450H	57	65	185	17,70

